


SuperLift 35 V2 Rotation Resistant 35X7

SuperLift 35 V2 (Double Compacted)				
Rope Diameter		Tensile	Weight	Minimum Breaking Load
Inches	MM			
	8	1960	0.216	6.5
	9	1960	0.270	8.13
	15	1960	0.730	22.9
5/8	15.87/16	1960	0.869	26.1
	18	1960	1.070	33.02
3/4	19	1960	1.251	36.97
	10	2160	0.337	10.87
	11	2160	0.410	12.22
	12	2160	0.492	14.7
1/2	12.5	2160	0.536	18.13
	14	2160	0.679	20.12
5/8	15.87/16	2160	0.878	28.2
	18	2160	1.108	35.9
3/4	19	2160	1.251	40.0
	19	ULTIMATE	1.251	42.9
	20	2160	1.382	44.6
	21	2160	1.510	48.45
7/8	22	2160	1.596	54.2
	23	2160	1.837	56.88
	24	2160	1.932	64.0
	25	2160	2.040	68.0
1	25.4	ULTIMATE	2.222	76.9
	26	2160	2.280	74.0
	26	ULTIMATE	2.334	79.3
	28	2160	2.630	82.6
	28	ULTIMATE	2.796	91.6
	30	2160	2.996	94.0
1-1/4	32	2160	3.430	110.2
	34	2160	3.860	126.0
	36	2160	4.521	144.0
	38	2160	4.784	157.0

- ◆ Double Compacted
- ◆ A flexible design multi-application hoist rope with high rotation resistance.
- ◆ Has both compacted inner and outer strands, resulting in higher break strengths.
- ◆ The rope is balanced design with a greater number of inner strands to counteract the torque of the outer stands.
- ◆ The core being of modern design, avoids crossovers between the strands of the core, reducing the risk of internal rope damage.
- ◆ Especially suited for mutli-layer spooling with its high crush and abrasion resistance.
- ◆ Able to be used with or without a swivel, resulting in no loss of breaking strength.
- ◆ Suitable for both single and multi-part line (reeving).
- ◆ Renowned for its excellent extended service life.



SuperLift 35 V2 (Double Compacted)