
## **Galvanized Cable**



#### All cable is manufactured in accordance with International Standard ASTM A 1023

### **Galvanized Cable**




7 X 7




7 V 10

CONSTRUCTION	7 X 7		7 X 19	
Diameter (in.)	Breaking Strength (lbs)	Weight per 1000 ft (lbs)	Breaking Strength (lbs)	Weight per 1000ft (lbs)
3/64	270	4.2	•••	
1/16	480	7.5	490	7.5
3/32	920	16	1,050	16
1/8	1,700	28	2,000	29
5/32	2,600	43	2,800	45
3/16	3,700	62	4,200	65
7/32	4,800	83	5,600	86
1/4	6,100	105	7,000	110
5/16	9,200	167	9,800	173
3/8	13,100	236	14,400	243
7/16			19,500	360

# Valuate ?



7 X 7



7 X 19

#### **PVC Coated Galvanized Cable**

Cable Diameter (in)	Coating Diameter (in)	Cable Construction	Breaking Strength (lbs)	Weight per 1000 ft (lbs)
1/16	3/32	7 X 7	480	9
3/32	1/8	7 X 7	920	18
1/8	3/16	7 X 7	1,700	35
3/16	1/4	7 X 7	3,700	74
1/8	3/16	7 X 19	2,000	36
3/16	1/4	7 X 19	4,200	77
1/4	5/16	7 X 19	7,000	123
5/16	3/8	7 X 19	9,800	197
3/8	7/16	7 X 19	14,400	270

Other cable and coating sizes available upon request

Galvanized Cable, normally referred to as "aircraft cable", is not intended for aircraft use. It is not certified to MIL-W-83420 because our cable does not go through all the testing requirements, notably the cycle test that is required to be on the federal governments QPL. All other testing and certifications are valid. Mill test certificates are provided upon request.