

V-LINE™

V-LINE 6' ENERGY ABSORBING LANYARD: DUAL LEG, REBAR HOOKS

FS88566-E

The V-Line 6' Energy Absorbing Lanyard combines performance with economical value. Built with abrasion resistant hi-vis orange webbing, efficient tear webbing to reduce fall arrest force and a durable cover. Includes dual leg for 100% tie-off, protective label cover and stamped steel hooks.

- 1" Polyester webbing
- [1] Stamped steel snap hook
- [2] Stamped steel rebar hooks
- Protective label cover
- Durable shock cover
- Dual leg construction
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502




High Performance Stitching



Dual Leg




Steel Snap Hook



Steel Rebar Hook



Durable Shock Cover



Hi-Vis Orange Webbing



V-Line 6' Energy Absorbing Lanyard: Rebar Hook

FS88565-E

- 1" Polyester webbing
- [1] Stamped steel snap hook
- [1] Stamped steel rebar hook
- Protective label cover
- Durable shock cover
- Single leg construction
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502



V-Line 6' Energy Absorbing Lanyard: Snap Hooks

FS88560-E

- 1" Polyester webbing
- [2] Stamped steel snap hooks
- Protective label cover
- Durable shock cover
- Single leg construction
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502



V-Line 6' Energy Absorbing Lanyard: Dual Leg, Snap Hooks

FS88561-E

- 1" Polyester webbing
- [3] Stamped steel snap hooks
- Protective label cover
- Durable shock cover
- Dual leg construction
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502



V-Line 3' Energy Absorbing Lanyard Snap Hooks

FS88560-E3

- 1" Polyester webbing
- [2] Stamped steel snap hooks
- Protective label cover
- Durable shock cover
- Single leg construction
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502

8256

VIEWPACK \ Web

– 6' Single Leg with 2 Snap Hooks.



- 8256 6' Length
- 8253 3' Length
- 8254 4' Length

82563

VIEWPACK \ Web

– 6- Single Leg with 1 Snap Hook and 1 Rebar Hook.



- 82563 6' Length
- 82543 4' Length

82562

VIEWPACK \ Web

– 6' Single Leg with 2 Snap Hooks and Tie-back D-ring.



- 82562 6' Length

8257

VIEWPACK \ Web

– 4½' to 6' Adjustable, Single Leg with 2 Snap Hooks.



- 8257 4½' to 6'

82608

VIEWPACK \ Web

– 6' Y-leg for 100% Tie-off; with 3 Snap Hooks.



- 82608 6' Length
- 826084 4' Length

826073

VIEWPACK \ Web

– 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



- 826073 6' Length
- 8260734 4' Length
- 8260733FT 3' Length

826082D

VIEWPACK \ Web

– 6' Y-leg for 100% Tie-off; 3 Snap Hooks and 2 Tie-back D-rings.



- 826082D 6' Length
- 826082D4 4' Length

8260732D

VIEWPACK \ Web

– 6' Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks; and 2 Tie-back D-rings.



- 8260732D 6' Length

826073ADJ

VIEWPACK \ Web

– 4½' to 6' Adjustable Y-leg for 100% Tie-off; with 1 Snap Hook and 2 Rebar Hooks.



- 826073ADJ 4½' to 6'

8106

VIEWPACK \ Rope

– 6' Single Leg, 5/8" Premium Polyester Rope, 2 Snap Hooks.



- 8106 6' Length
- 8103 3' Length
- 8104 4' Length

82563A

VIEWPACK \ Aluminum

– 6' Single Leg; with 1 Aluminum Snap hook and 1 Aluminum Rebar Hook.



- 82563A 6' Length

826073A

VIEWPACK \ Aluminum

– 6' Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks.



- 826073A 6' Length

826073A2D

VIEWPACK \ Aluminum

– 6' Y-leg for 100% Tie-off; with 1 Aluminum Snap Hook and 2 Aluminum Rebar Hooks and 2 Tie-back D-rings.



- 826073A2D 6' Length

825623A

VIEWPACK \ Aluminum

– 6' Single Leg; with 1 Aluminum Snap Hook and 1 Aluminum Rebar Hook and Tie-back D-ring.



- 825623A 6' Length

8150

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 1 Snap Hook and Braid-end.



- 8150 50' Length
- 8125 25' Length
- 8175 75' Length
- 8200 100' Length
- 8150S 150' Length
- 8200S 200' Length

8149

ROPE \ Lifelines

– 50' x 5/8" Copolymer Rope; with 1 Snap Hook and Braid- or Taped-end.



- 8149 Braid-end
- 8149T Taped-end

8150T

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 1 Snap Hook and Taped-End.



- 8150T 50' Length
- 8120T 20' Length
- 8125T 25' Length
- 8130T 30' Length
- 8175T 75' Length
- 8200T 100' Length

8150DH

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; with 2 Snap Hooks.



- 8150DH 50' Length
- 8125DH 25' Length
- 8175DH 75' Length
- 8200DH 100' Length

8151

ROPE \ Lifelines

– 50' x 5/8" Premium Polyester Rope; Thimble and Braid-End.



- 8151 50' Length
- 8126 25' Length
- 8201 100' Length
- 8151T 50' Length

7120

COUNTER WEIGHT

– Counter Weight; 5 lbs for Vertical Lifelines; Chokes to Trailing End to Keep Line Taught.




– 7120

8447

STEEL \ Carabiner

– Large Twist Lock; 2 1/4" Opening; 3,600 lbs Gate; with Captive Pin Option.




– 8447

8445

STEEL \ Carabiner

– Compact Twist Lock; 7/8" Opening; 3,600 lbs Gate.




– 8445

8450

STEEL \ Carabiner

– Medium Twist Lock; 1" Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8450

83662D

D-RING EXTENDERS \ Extenders

– 18" Web with Snap Hook and 2nd D-ring for SRL Attachment.




– 83662D 18"

8447A

ALUMINUM \ Carabiner

– Large Twist Lock; 2" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8447A

8466A

ALUMINUM \ Carabiner

– Medium Twist Lock; 7/8" Gate Opening; 3,600 lbs Gate; with Captive Pin Option.



– 8466A

8366

D-RING EXTENDERS \ Extenders

– 18" Web with Snap Hook and D-ring.



- 8366 18"
- 8202 14"
- 836616 16"
- 836624 24"

8366L

D-RING EXTENDERS \ Extenders

– 18" Web with Choking Loop and D-ring.



– 8366L 18"

**18" D-RING EXTENDER:
REBAR HOOK, D-RING**
FS814

The 18" D-Ring Extender provides additional length between the harness dorsal D-ring and connection to another component of the fall arrest system. Includes convenient rebar hook end and opposite D-ring end for quick, easy connection.

- 18" Set length
- [1] Forged rebar hook
- [1] Forged steel D-ring
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502



Flexible Connection



Steel D-Ring



Forged Rebar Hook



**18" D-Ring Extender:
Snap Hook, D-Ring**
FS813

- 18" Set length
- [1] Forged steel snap hook
- [1] Forged steel D-ring
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.3, ANSI A10.32, OSHA 1926.502



2D-Ring Option

PART NUMBER	DESCRIPTION
FS813-2D	18" D-ring Extender: Snap Hook, 2 D-rings



**18" Energy Absorber:
Snap Hook, D-Ring**
FS8800SP-D

- 18" Set length
- [1] Forged steel D-ring
- [1] Forged steel snap hook
- Protective label cover
- Durable shock cover
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502



**18" D-Ring Extender:
Soft Loop, D-Ring**
FS813-LOOP

- 18" Set length
- [1] Soft choke loop
- [1] Forged steel D-ring
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.3, ANSI A10.32, OSHA 1926.502



**20" Energy Absorber:
Soft Loop, Snap Hook**
FS8800SP-L

- 20" Set length
- [1] Soft choke loop
- [1] Forged steel snap hook
- Protective label cover
- Durable shock cover
- Capacity 130-310 lb.
- Minimum breaking strength 5,000 lbs.
- Meets ANSI Z359.13, ANSI A10.32, OSHA 1926.502