



FS99160-EFD

V-Line Construction Harness : 3D, MB Chest, FD, TB Legs

FEATURES :

- Dorsal D-ring
- Front D-ring
- Side positioning D-rings
- Mating buckle chest
- Friction buckle torso adjusters
- Tongue buckle legs
- Shoulder pad
- Floating waist pad

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

**ITEM WEIGHT :**

- 5.6 lbs. (2.5 kg)

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
FS99160-EFD-S	Small
FS99160-EFD-M	Medium
FS99160-EFD-L	Large
FS99160-EFD-XL	X-Large
FS99160-EFD-2X	2X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Zinc plated alloy steel
Adjuster buckles	Zinc plated alloy steel
Chest connection	Zinc plated alloy steel
Leg connection	Steel tongue buckle w/ SS grommets
Pads	Polyester mesh; EVA
Belt	Polyester; Steel; Stainless steel



FS99185-E

V-Line Full Body Harness : Universal, 1D, MB Chest, TB Legs

FEATURES :

- Dorsal D-ring
- Mating buckle chest
- Mating buckle torso adjusters
- Tongue buckle legs
- Shoulder pad

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 4.0 lbs. (1.8 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
FS99185-E	Universal
FS99185-E-2X	2X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring	Zinc plated alloy steel
Adjuster buckles	Zinc plated alloy steel
Chest connection	Zinc plated alloy steel
Leg connection	Steel tongue buckle w/ SS grommets
Pad	Polyester mesh; EVA



020-1220 through 020-1226

PRO+ Slate Full Body Harness : Alu 1D, Alu QC Chest/Legs

FEATURES :

- Dorsal D-ring
- Dorsal SRL link
- Quick-connect chest
- Quick torso adjusters
- Quick-connect legs
- Shoulder pad
- Removable leg pads

FALL ARREST POINT(S) :

- 1 Dorsal D-ring
- 1 Dorsal SRL link

ITEM WEIGHT :

- 4.4 lbs. (2.0 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
020-1220	X-Small
020-1221	Small
020-1222	Medium
020-1223	Large
020-1224	X-Large
020-1225	2X
020-1226	3X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring	Anodized aluminum
Adjuster buckles	Anodized aluminum
Chest connection	Anodized aluminum
Leg connection	Anodized aluminum
Dorsal SRL link	Polyester
Pads	Nubuck synthetic; Spandex; Poly mesh; EVA



021-1617 through 021-1621

V-Line Construction Harness : 3D, QC Chest, TB Legs

FEATURES :

- Dorsal D-ring
- Side positioning D-rings
- Quick-connect chest
- Friction buckle torso adjusters
- Tongue buckle legs
- Shoulder pad
- Floating waist pad

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 5.5 lbs. (2.5 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
021-1617	Small
021-1618	Medium
021-1619	Large
021-1620	X-Large
021-1621	2X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Zinc plated alloy steel
Adjuster buckles	Zinc plated alloy steel
Chest connection	Zinc plated alloy steel
Leg connection	Steel tongue buckle w/ SS grommets
Pads	Polyester mesh; EVA
Belt	Polyester; Steel; Stainless steel

Features :

- New ergonomic lateral leg straps and construction greatly improve comfort and mobility. No more disconnecting leg straps when not in use.
- Rugged waist belt supports extreme loads of tools or equipment without folding while distributing load evenly for improved comfort
- Reinforced sub-pelvic strap features durable wear pad for extended product service life
- New ArrowGrip dorsal D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day
- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Updated SRL connection point allows for fast, hassle-free attachment of all types of single and twin SRLs
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Quick-connect chest buckle features visual indicator showing positive connection
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2021



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	ANSI	Z359.11-2021
D-rings	Aluminum alloy; 5,000 lb min. static strength	ANSI User Capacity	133 to 310 lb max.	OSHA	1926.502 and 1910.66
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	133 to 425 lb max.	CSA	Z259.10-2018
Sizes & Part Numbers					
8144XS - XS	8144SM - Dual-size Small/Med	8144LXL - Dual-size Large/XL	81442X3X - Dual-size 2X/3X		

Features :

- Features integral vented and padded hard-shell shoulder yoke and 6" waist support positioning pad to provide user comfort
- Includes alloy steel D-rings, friction roller torso adjusters, tongue buckle legs, and quick-connect chest closures.
- Features integrated soft-sling suspension and positioning seat
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect buckle features visual indicators showing positive connection
- Paired lanyard parking keepers provide balanced function for lanyards and personal SRLs
- Includes fully adjustable suspension trauma relief system
- Complies with ANSI Z359.11-2014



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	CSA	Z259.10-2018
D-rings	Plated alloy steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	ANSI	Z359.11-2014
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.	OSHA	1926.502 and 1910.66

Sizes & Part Numbers				
7042S - Small	7042M - Medium	7042L - Large	7042XL - XL	

Features :

- Features all-black plated alloy steel hardware for refined, low profile look
- V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day
- Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back reducing fatigue
- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs provide quick and simple lower-body adjustment
- Includes suspension trauma relief straps
- Complies with ANSI Z359.11-2021



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	ANSI	Z359.11-2021
D-ring	Plated alloy steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	OSHA	1926.502 and 1910.66
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.	CSA	Z259.10-2018
Sizes & Part Numbers					
7008CXS - XS	7008CSM - Dual-Size Small/Med	7008CLX - Dual-Size Large/XL	7008C2X3X - Dual-Size 2XL/3XL		

Features :

- Features all-black plated alloy steel hardware for refined, low profile look
- V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day
- Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back reducing fatigue
- Features integral tri-layer padded shoulder yoke to provide breathable user comfort
- Heavy duty waist pads provides support without folding for improved comfort
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs provide quick and simple lower-body adjustment
- Includes suspension trauma relief straps
- Complies with ANSI Z359.11-2021



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	ANSI	Z359.11-2021
D-ring	Plated alloy steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	OSHA	1926.502 and 1910.66
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.	CSA	Z259.10-2018
Sizes & Part Numbers					
7078CXS - XS	7078CSM - Dual-Size Small/Med	7078CLX - Dual-Size Large/XL	7078C2X3X - Dual-Size 2XL/3XL		

Features :

- Features premium overmolded alloy steel dorsal D-ring and mating buckle torso adjusters
- Economical leather insulated quick-connect leg and chest buckles also included.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso and legs
- Quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength	Static Strength	3,600 lb min.	ASTM	F887
D-ring	Overmolded Alloy Steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	ANSI	Z359.11-2014
Buckles and Adjusters	Overmolded and plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.	OSHA	1926.502 and 1910.66
Sizes & Part Numbers					
8076 - UniFit (S, M, L)	8076XL - XL				