

QUADRUPLE LEG



TL4-CQ



TL4-CL



TL4-EQKN



TL4-BKG



TG4-CL



TG4-CQ



TG4-EQKN



TG4-P



TG4-BKG

TOP LOK TYPE TL4

Assembly required for 4-Leg, non-adjustable sling



Model	Components Required	Chain Size Inches	Working Load Limit *(Lbs) at 60°	L (In)	Weight Each (Lbs)
TL4-8-10	MF-1310-10 + 2 CLD- 8-10	5/16"	14,800	8.5	6.8
TL4-10-10	MF-1613-10 + 2 CLD-10-10	3/8"	22,900	10.3	11.5
TL4-13-10	MF-2016-10 + 2 CLD-13-10	1/2"	39,000	13.2	25.3
TL4-16-10	MF-2220-10 + 2 CLD-16-10	5/8"	58,700	14.4	42.3

*Design factor 4

TOP GRAB TYPE TG4

Assembly required for 4-Leg fully adjustable sling

Model	Components Required	Chain Size Inches	Working Load Limit *(Lbs) at 60°	L (In)	Weight Each (Lbs)
TG4-8-10	MF-1310-10 + 2 CGD- 8-10	5/16"	14,800	10.5	9.0
TG4-10-10	MF-1613-10 + 2 CGD-10-10	3/8"	22,900	12.7	15.9
TG4-13-10	MF-2016-10 + 2 CGD-13-10	1/2"	39,000	16.3	35.5
TG4-16-10	MF-2220-10 + 2 CGD-16-10	5/8"	58,700	18.3	60.8

*Design factor 4

